



EC DECLARATION OF PERFORMANCE

(System 3)

Issue No: **1**

13

Starglaze Windows & Conservatories Ltd.
 Sternfenster upvc.
 The Works,
 Waterside South,
 Lincoln,
 LN5 7JD

This document declares that the product:

Upvc Residential Door {non escape route}

System Description: *Deceuninck 2800*


External pedestrian doorset intended to be used in domestic and commercial buildings, conforming to the product requirements of BS EN 14351-1:2006+A1:2010 Annex ZA

Essential Characteristics	Performance	Test Standards	Name, Address and Notified Body No of Test Laboratory	Test report reference and issue date
Watertightness	npd	BS EN 1027	N/A	N/A
Dangerous substances	None	BS EN 14351-1:2006+A1:2010	N/A	In house declaration
Resistance to wind load	npd	BS EN 12211	N/A	N/A
Impact resistance	npd	BS EN 13049	N/A	N/A
Load-bearing capacity of safety devices	Not Fitted	N/A	N/A	N/A
Height (mm)	npd	BS EN 14351-1:2006+A1:2010	N/A	N/A
Ability to release	npd	BS EN 179 and BS EN 1125	N/A	N/A
Acoustic performance	npd	BS EN ISO 140-3	N/A	N/A
Thermal transmittance	1.36Wm2k	EN ISO 10077-1 & EN ISO 10077-2 (or EN ISO 12567-1 and prEN 12567-2)	BSI Group, Kitemark Court, Davy Avenue, Knowlhill, Milton Keynes, MK5 8PP	7842820 25.6.12
Radiation properties	npd	EN 410	N/A	N/A
Air permeability	npd	BS EN 1026	N/A	N/A

This declaration of performance is issued under the sole responsibility of *Starglaze Windows & Conservatories Ltd.*


Signed on behalf of *Starglaze Windows & Conservatories Ltd* :

Signature:



Name and Position: M E Parczuk, Managing Director

Date: 20th June 2013

	
Starglaze Windows & Conservatories Ltd.	
13	
REF:DECU2800RD	
BS EN 14351-1:2006+A1:2010	
<i>Upvc Residential Door Deceuninck 2800</i> Intended use not on an escape route	
Water tightness	NPD
Dangerous substances	None
Resistance to wind load	NPD
Load bearing capacity of safety device	N/A
Acoustic performance	NPD
Thermal transmittance	$\leq 1.36 \text{ W/m}^2\text{K}$
Radiation properties	NPD
Air permeability	NPD